

|   |                         |
|---|-------------------------|
| Model   | C1302 crawler tractor   |
| Overall dimensions(LxWxH) mm  |                         |
| Without dozer blade   | 5344×1835×2786          |
| With dozer blade  | 5367×2462×2786          |
| Wheelbase mm  | 2774                    |
| Track mm  | 1435                    |
| Track shoe width mm   | 390                     |
| Service mass kg   |                         |
| Without dozer blade   | 7300                    |
| With dozer blade  | 7550                    |
| Ground pressure kPa   |                         |
| Without dozer blade   | 46.75                   |
| With dozer blade  | 48.35                   |
| Speed, tractive force, forward gears(6F+2Rengagement sleeve transmission) |                         |
| Gear I (km/h)/tractive force(kN)  | 3.71/52.9               |
| Gear II (km/h)/tractive force (kN)  | 6.859/32.5              |
| Gear III (km/h)/tractive force (kN)                                       | 7.798/32.2              |
| Gear IV (km/h)/tractive force (kN)  | 8.996/27                |
| Gear V (km/h)/tractive force (kN)   | 10.591/22               |
| Gear VI (km/h)/tractive force (kN)  | 13.917/14.3             |
| Reverse speed gear I (km/h)   | 3.314                   |
| Reverse speed gear II (km/h)  | 6.289                   |
| Engine model  | LR6A3Z-22 diesel engine |
| Rated power kW  | 95.6                    |
| Rated speed r/min   | 2200                    |
| Dozer blade type  | fixed straight blade    |
| HxW mm  | 850×2462                |
| Depth into soil mm  | >290                    |
| Max. lifting height mm  | >625                    |